

### Description

Repsol ATFluid IIIH is a durable, synthetic lubricant developed for automatic transmissions. It is suitable for light vehicles, commercial vehicles, and equipment in the public work sector. This product is highly recommended for transmissions and power-assisted steering that require a fluid compatible with GM Dexron III specifications.

### Properties

- This formulation improves performance and service life compared to the formula of previous automatic transmission fluids (ATF), thus reducing the need for maintenance and increasing the drain oil interval.
- It has excellent oxidation resistance property which lowers deposit formation and prolongs transmission life.
- Its inclusion of friction modifiers in its formulation ensures smooth gear change and efficient power transfer under all service conditions.
- The product's high friction stability characteristic facilitates energy saving as compared to other ATFs.
- ATFluid III is compatible with most rubber joints and seals.

### Quality Levels

- GM DEXRON III H

### Technical Specifications

	UNIT	METHOD	VALUE
Colour		Visual	Red
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.844
Viscosity at 100 °C	cSt	ASTM D 445	7.3
Viscosity at 40 °C	cSt	ASTM D 445	34
Viscosity at -40 °C	cP	ASTM D 2983	20000 max.
Viscosity index	-	ASTM D 2270	181
Flash point, open cup	°C	ASTM D 92	226
Pour point	°C	ASTM D 97	-51

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety data file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS302. Revision 1. May 2020.