

DIESEL SERIE 3 10W



TRANSMISSIONS AND GEARBOXES

Lubricants

Description

High quality monograde mineral lubricant oil formulated from a very hydrotreated refined base oil. Thanks to the additive technology used, the DIESEL SERIE 10W product reaches outstanding resistance to oxidation, anti-wear performance and detergency/dispersance to keep all the equipments clean and protected.

It may be used as a hydraulic fluid in public works machinery, and in transmissions in which the manufacturer recommends this viscosity grade.

Properties

- Significant detergent-dispersant power, which prevents the formation of deposits.
- Significant improvements in anticorrosion and antirust properties, which ensures better protection of the metallic elements in the application.
- Low pour point for smoother start and stop.
- Excellent antifoam properties.
- Excellent performance with seals and elastomers, which ensures greater compatibility with the different parts of the hydraulic system.

Quality levels

- API CF4/SG
- CATERPILLAR TO-2
- ALLISON C-3

Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			10W
Density at 15 °C	g/mL	ASTM D 4052	0.883
Viscosity at 100 °C	cSt	ASTM D 445	6.6
Viscosity at 40 °C	cSt	ASTM D 445	39
Viscosity index	-	ASTM D 2270	110
Flash point, open cup	°C	ASTM D 92	200 min.
Pour point	°C	ASTM D 97	-27
T.B.N.	mg KOH/g	ASTM D 2896	10
Sulphated ash	% in weight	ASTM D 874	1.5

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Technical data sheet for Lubricant RNG102. Revision 1. March 2020.