

## Description

REPSOL GXR 3 is a quality multi-grade lubricant oil formulated with mineral base oils for a wide range of usage. It is recommended for both gasoline and diesel engines; passenger cars and industrial vehicles. It is ideal for urban services and public works with standard oil changes intervals. It is notable for its very low consumption and good protection at elevated temperatures.

## Properties

- Multi-grade oil that keeps the engine clean
- Its high viscosity helps to seal the engine and prevent leaks
- Its formulation minimizes deposits formation.
- The oil exhibits excellent anti-wear properties
- It can be used in warm environment, providing good lubrication to different parts of the engine.

## Quality levels

- API SG/CD

## Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			20W-50
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.875
Viscosity at 100 °C	cSt	ASTM D 445	17,7
Viscosity at 40 °C	cSt	ASTM D 445	163
Viscosity at -15 °C	cP	ASTM D 5293	9500 max.
Viscosity index	-	ASTM D 2270	120
Flash point, open cup	°C	ASTM D 92	225 min.
Pour point	°C	ASTM D 97	-24min
T. B. N.	mg KOH/g	ASTM D 2896	5,2
Noack volatility, 1hr at 250 °C	% weight	DIN 51581	15 max.

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety data sheet is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RAS004. Revision 1. March 2020.