

Description

Repsol MXR Matic is a lubricant for four-stroke engines, developed to meet the requirements of the most important motorcycle manufacturers. For use in automatic scooters only, this product is equipped with friction modifiers that allows it to protect the engine while reducing friction and fuel consumption. Lower friction also means a more optimal power output and a more agile engine as a result.

Properties

- Superior protection for the engine against wear and deposit formation.
- Strong durability due to excellent engine protection, cleanliness and thermal reliability, improving the engine's life.
- Outstanding low friction performance which increases fuel efficiency.
- Reduces deposits on the spark plug and prevents the piston rings from sticking.

Quality Levels

- JASO T903:2016: MB
- API SJ

Technical Specifications

	UNIT	METHOD	10W-30	10W-40	20W-40
SAE GRADE			10W-30	10W-40	20W-40
Density at 15 °C	g/mL	ASTM D 4052	0.852	0.866	0.881
Viscosity at 100 °C	cSt	ASTM D 445	11,1	14,1	15.4
Viscosity at 40 °C	cSt	ASTM D 445	75	90	100
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.	7000 max.	
Viscosity at -15 °C	cP	ASTM D 5293			9500
Viscosity index	-	ASTM D 2270	141	148	148
Flash point, open cup	°C	ASTM D 92	220	200	224
Pour point	°C	ASTM D 97	-15 max.	-15 max.	-12 max
T. B. N.	mg KOH/g	ASTM D 2896	6,0	6,0	6,0

The above-mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com
+34 901 111 999
lubricantes@repsol.com

Technical data sheet for Lubricant RAS202. Revision 1. March 2020.